

Key Benefits

- Multivariable vortex flowmeter for measuring volumetric flow, temperature, pressure, density, and mass flow using a single meter
- Measures most gases, liquids and steam without the need to recalibrate
- Advanced design and digital signal processing for vibration isolation
- Cost effective, accurate and reliable meter for volumetric and mass flow measurement for pipe sizes from ½ in to 8 in (15 mm to 200 mm)
- Energy management through accurate measurement of both temperature and mass flow simultaneously
- Remote monitoring and integration to DCS using HART® and Modbus® communication protocols
- Significant cost savings through reduced installation costs, wiring runs and services support using MV meter with no moving parts
- FM USA/Canada-approved, explosion-proof and dust ignition-proof

Applications

- Ideal for high temperature and high velocity steam
- Power Generation—steam applications
- Industrial—HVAC, district energy management
- Commercial—building, campus and facility energy management
- Oil & gas—allocation of natural gas
- Petrochemical—mass balancing, reaction processes heating

PanaFlow™ MV82

Insertion Multivariable
Flowmeter for Mass,
Temperature, and
Pressure



GE Sensing

Unique Multivariable Design

GE Sensing's PanaFlow MV82 Insertion Multivariable Mass Vortex flowmeter is the next generation vortex meter. PanaFlow MV82's multivariable design consists of a vortex shedding velocity sensor, an RTD temperature sensor and a solid state pressure transducer that measures the mass flow rate of steam, gases and liquids.

Other meter types use external process measurements to calculate mass flow. The temperature and pressure devices are typically not installed in the same location as the flowmeter. Process conditions can vary greatly between the two locations causing inaccurate mass flow readings. PanaFlow MV82 measures velocity, temperature and pressure at the same location, which provides more accurate process measurement.

Simple and Cost Effective

Integrating pressure and temperature into the vortex flowmeter simplifies system complexity and helps minimize initial capital costs, as well as reduces the installation costs. There is no need to purchase additional instrumentation to monitor pressure and temperature since the PanaFlow MV82 will output all parameters to your data acquisition system.

The product line is available with a wide range of options and meter configurations to meet your specific application requirements.

Portfolio of Flowmeter Solutions

GE Sensing is committed to providing customers with the best technologies for their flow measurement needs. PanaFlow MV82 is the newest addition to the PanaFlow family of flowmeters, providing effective solutions for smaller pipe sizes for a variety of applications. GE Sensing offers the PanaFlow MV82 in a number of configurations to best suit your application measurement needs.

PanaFlow MV82-VTP

The MV82-VTP offers flow computer functionality in a compact field device. This multivariable instrument incorporates temperature and pressure sensors to provide an instantaneous reading of compensated mass flow rate of gases, liquids and steam. In addition to outputs for totalized mass and alarm settings, the field-configurable electronics deliver up to three analog 4-20 mA outputs of five process measurements, including volumetric flow rate, mass flow rate, pressure, temperature and density.

PanaFlow MV82-VT

The MV82-VT integrates a precision 1000 ohm platinum RTD temperature sensor used to calculate and output a compensated mass flow reading. This device is typically used to measure flow rates of saturated steam.

PanaFlow MV82-V

The MV82-V delivers a direct reading of volumetric flow rate—generally the most cost-effective solution for liquid flow monitoring—in applications ranging from general water flows to hydrocarbon fuel flow measurement.

PanaFlow MV82-EM

The MV82-EM energy monitoring option enables real time calculation of energy consumption for a facility or process. The meter can be programmed to measure steam, hot water or chilled water. This option uses the MV82-EM flowmeter to monitor one side of the process, either sent or return, and uses the input from a second separate temperature sensor on the opposite leg of the process to calculate the change in energy. Selectable energy units include BTU, joules, calories, Watt-hours, Megawatt-hours and Horsepower-hours. The local or remote electronics indicate two temperatures, delta T, mass total and energy total.

PanaFlow MV82 Specifications

Performance

Accuracy

Mass flow rate accuracy for gas and steam based on 50-100% of pressure range.

PanaFlow MV82 Accuracy Flowmeter		
Process Variables	Liquids	Gas and Steam
Volumetric Flow Rate	± 1.2% of Rate	± 1.5% of Rate
Mass Flow Rate	± 1.5% of Rate	± 2.0% of Rate
Temperature	± 2°F (± 1°C)	± 2°F (± 1°C)
Pressure	± .3% of Full Scale	± .3% of Full Scale
Density	± .3% of Reading	± .5% of Reading

Repeatability

Mass Flow Rate	± 0.2% of rate
Volumetric Flow Rate	± 0.1% of rate
Temperature	± 0.2°F (± 0.1°C)
Pressure	± 0.05% of full scale
Density	± 0.1% of reading

Stability Over 12 Months

Mass Flow Rate	± 0.2% of rate
Volumetric Flow Rate	negligible
Temperature	± 0.9°F (± 0.5°C)
Pressure	± 0.1% of full scale
Density	± 0.1% of reading

Response Time

Adjustable from 1 to 100 seconds

Operating

Process and Ambient Temperature

Process Standard Temperature (code ST):	-40 to 500°F (-40 to 260°C)
Process High Temperature (code HT):	Up 750°F (400°C)
Ambient Operating:	-5 to 185°F (-20 to 85°C)
Ambient Storage:	-40 to 185°F (-40 to 85°C)

Pressure Transducer Ratings			
Full Scale Operating Pressure		Max. Over-Range Pressure	
psia	bara	psia	bara
30	2	60	4
100	7	200	14
300	20	600	40
500	35	1000	70
1500	100	2500	175

Pressure Ratings			
Style Connection	Process	Rating	Ordering
	2-inch (50mm) Male NPT	ANSI 600 lb	CNPT
	2-inch 150 lb (50mm 70kg) flange	ANSI 150 lb (50kg)	C150
	2-inch 300 lb (50mm 135kg) flange	ANSI 300 lb (135kg)	C300
	2-inch 600 lb (50mm 275kg) flange	ANSI 600 lb (275kg)	C600
Packing Gland	2-inch (50mm) Male NPT	50 Psig (3.5 BarG)	PNPT
	2-inch 150 lb (50mm 70kg) flange	50 Psig (3.5 BarG)	P150
	2-inch 300 lb (50mm 135kg) flange	50 Psig (3.5 BarG)	P300
Packing Gland and Removable Retractor	2-inch (50mm) Male NPT	ANSI 300 lb (135kg)	PNPT and RR
	2-inch 150 lb (50mm 70kg) flange	ANSI 150 lb (70kg)	P150 and RR
	2-inch 300 lb (50mm 135kg) flange	ANSI 300 lb (135kg)	P300 and R
Packing Gland and Permanent Retractor	2-inch (50mm) Male NPT	ANSI 600 lb (275kg)	PNPTR
	2-inch 150 lb (50mm 70kg) flange	ANSI 150 lb (70kg)	P150R
	2-inch 300 lb (50mm 135kg) flange	ANSI 300 lb (135kg)	P300R
	2-inch 600 lb (50mm 275kg) flange	ANSI 600 lb (275kg)	P600R

Power Requirements

Model M82-V: 12-36 VDC loop powered

Model M82-VTP, DC option: 12-36 VDC, 100 mA max

Model M82-VTP, AC option: 85-240 VAC, 50/60Hz, 1 Watt

Display

Alphanumeric 2 line x 16 character LCD digital display

Six pushbuttons for full field configuration

Pushbuttons can be operated with magnetic wand without removal of enclosure covers

Display can be mounted in 90° intervals for better viewing

Output Signals

Analog: 4-20 mA, loop powered for volumetric meters

Alarm: Solid state relay, 40 VDC

Totalizer Pulse: 50 millisecond, 40 VDC

Volumetric: One analog, one totalizer pulse, HART

Multivariable: Up to three analog signals, three alarms, one totalizer pulse, HART

Multivariable option: Modbus process monitoring

PanaFlow MV82 Specifications

Physical

Wetted Materials

316L stainless steel, plus:

- PTFE-based thread sealant on models with pressure transducer
- PTFE packing on standard temperature models with packing gland
- Graphite-based packing on high temperature models with packing gland

FM USA/Canada Approvals

Explosion-proof for Class I, Division 1, Groups B, C & D
Dust-ignitionproof for Class II/III, Division 1, Groups E, F & G

Type 4x and IP66

T6 at Tamb = 140°F (60°C)

Sizing Considerations

Piping Conditions		
Condition	Pipe Diameters, D	
	Upstream	Downstream
One 90° elbow before meter	10D	5D
Two 90° elbows before meter	15D	5D
Two 90° elbows before meter, out of plane	25D	5D
Reduction before meter	10D	5D
Expansion before meter	20D	5D
Partially open valve	25D	5D

Velocity Range

Maximum velocity, liquid: 30 feet/sec (9 meters/second)

Minimum velocity, liquid: 1 foot/sec (.3 meters/second)

Maximum velocity, gas or steam: 300 feet/sec (90 meters/second)

Minimum velocity, gas or steam feet/sec (meters/second):

$$\frac{5}{\sqrt{\text{density (Lb/ft}^3\text{)}}}$$

$$\frac{6.1}{\sqrt{\text{density (kg/m}^3\text{)}}}$$

Consult the PanaFlow MV Sizing Program for easy calculation of flow range.

Water Minimum and Maximum Flow Rates						
Rate	Nominal Pipe Size (in)					
	3	6	8	12	16	24
GPM min	20.6	81.3	142	317	501	1138
GPM max	618	2437	4270	9501	15043	34144
	Nominal Pipe Size (mm)					
	80	150	200	300	400	600
M ³ /hr min	5.2	20.4	35.4	79.2	125	284
M ³ /hr max	157	614	1062	2337	3753	8537

PanaFlow MV82 Specifications

Typical Saturated Steam Minimum and Maximum Flow Rates (lb/hr)						
Pressure	Nominal Pipe Size (in)					
	3	6	8	12	16	24
5 psig	205	800	1385	3099	4893	11132
	2721	10633	18412	41196	65039	147954
100 psig	468	1831	3170	7092	11197	25472
	14246	55674	96407	215703	340546	774698
200 psig	632	2471	4278	9572	15111	34377
	25948	101405	175595	392880	620268	1411029
300 psig	762	2976	5153	11530	18203	41410
	37652	147145	254799	570093	900047	2047489
400 psig	873	3412	5908	13219	20870	47477
	49494	193420	334930	749382	1183103	2691404
500 psig	974	3805	6588	14741	23272	52942
	61543	240507	416468	931816	1471125	3346615

Typical Air Minimum and Maximum Flow Rates (SCFM) Air at 70°F						
Pressure	Nominal Pipe Size (in)					
	3	6	8	12	16	24
0 psig	56	220	381	852	1345	3059
	924	3611	6253	13991	22089	50250
100 psig	157	615	1065	2383	3763	8560
	7236	28279	48969	109564	172977	393500
200 psig	216	843	1460	3266	5156	11729
	13588	53101	91950	205732	324804	738886
300 psig	262	1022	1770	3960	6251	14221
	19974	78059	135169	302430	477467	1086176
400 psig	301	1175	2034	4551	7186	16346
	26391	103136	178593	399588	630859	1435121
500 psig	335	1310	2269	5077	8015	18233
	32834	128314	222191	497136	784865	1785464

Typical Saturated Steam Minimum and Maximum Flow Rates (kg/hr)						
Pressure	Nominal Pipe Size (mm)					
	80	150	200	300	400	600
0 barg	81	316	548	1226	1936	4404
	938	3667	6350	14209	22432	51039
5 barg	187	729	1263	2826	4461	10151
	4946	19486	33742	75495	119189	271187
10 barg	249	972	1683	3767	5947	13530
	8859	34620	59949	134132	211764	481821
15 barg	298	1164	2016	4510	7120	16200
	12700	49629	85939	192283	303570	690705
20 barg	340	1329	2301	5148	8128	18493
	16550	64676	111995	250581	395609	900119
30 barg	413	1612	2791	6246	9860	22435
	24357	95187	164827	368789	582234	582234


Typical Air Minimum and Maximum Flow Rates (nm ³ /hr) Air at 20°C						
Pressure	Nominal Pipe Size (mm)					
	80	150	200	300	400	600
0 barg	89	347	601	1345	2124	4833
	1463	5716	9897	22145	34962	79547
5 barg	217	847	1467	3282	5181	11788
	8702	34006	58885	131751	208004	473266
10 barg	294	1148	1987	4446	7020	15972
	15975	62430	108105	241878	381870	868857
15 barg	355	1385	2399	5368	8474	19282
	23280	90979	157542	352487	556497	1266182
20 barg	407	1589	2751	6156	9718	22112
	30615	119642	207175	463539	731823	1665095
30 barg	495	1934	3349	7493	11829	26915

Turndown

Turndown is application-dependent. Consult the PanaFlow MV Sizing Program for exact values. Turndown can exceed 100:1.

PanaFlow MV82 Specifications

Dimensional Outline: Compression Fitting Models



Approximate Weight, lb (kg)


	CL	SL	EL
CNPT	13 (5.7)	14 (6.2)	15 (6.7)
C150	15 (6.8)	16 (7.3)	17 (7.8)
C300	17 (7.8)	18 (8.3)	19 (8.8)
C600	18 (8.2)	19 (8.)	20 (9.2)

Add 11 lb (5 kg) for remote electronics

PanaFlow MV82-V, VT in (mm) CL/Compact Length	CL/Compact Length		SL/Standard Length		SL/Extended Length	
	A	B	A	B	A	B
CNPT, Compression Fitting, Male NPT	21.6 (549)	9.8 (249)	38 (965)	26.2 (665)	50 (1270)	38.2 (970)
C150, Compression Fitting, 150 lb Flange	21.6 (549)	10.9 (277)	38 (965)	27.3 (693)	50 (1270)	39.3 (998)
C300, Compression Fitting, 300 lb Flange	21.6 (549)	10.8 (277)	38 (965)	27.2 (691)	50 (1270)	39.2 (996)
C600, Compression Fitting, 600 lb Flange	21.6 (549)	10.4 (264)	38 (965)	26.8 (681)	50 (1270)	38.8 (986)

PanaFlow MV82-V, VT in (mm) CL/Compact Length	SL/Compact Length		SL/Standard Length		EL/Extended Length	
	A	B	A	B	A	B
CNPT, Compression Fitting, Male NPT	24.6 (625)	9.8 (249)	41 (1041)	26.2 (665)	53 (1346)	38.2 (970)
C150, Compression Fitting, 150 lb Flange	24.6 (625)	10.9 (277)	41 (1041)	27.3 (693)	53 (1346)	39.3 (998)
C300, Compression Fitting, 300 lb Flange	24.6 (625)	10.8 (274)	41 (1041)	27.2 (691)	53 (1346)	39.2 (996)
C600, Compression Fitting, 600 lb Flange	24.6 (625)	10.4 (264)	41 (1041)	26.8 (681)	53 (1346)	39.8 (986)

Dimensional Outline: Packing Gland Models



PanaFlow MV82 in (mm)	SL/Standard Length		EL/Extended Length	
	A	B	A	B
PNPT, Packing Gland, Male NPT	40.5 (1029)	21.5 (546)	52.5 (1334)	33.5 (851)
P150, Packing Gland, 150 lb Flange	40.5 (1029)	21.1 (536)	52.5 (1334)	33.1 (841)
P300, Packing Gland, 300 lb Flange	40.5 (1029)	21.1 (536)	52.5 (1334)	33.1 (841)


Approximate Weight, lb (kg)

	SL	EL
PNPT	16 (7.1)	17 (7.6)
P150	21 (9.4)	22 (9.9)
P300	25 (11.3)	26 (11.8)


Add 11 lb (5 kg) for remote electronics

PanaFlow MV82 Specifications

Dimensional Outline: Packing Gland Models with Permanent Retractor



Dimensional Outline: Remote Electronics Option



PanaFlow MV82 in (mm) With Permanent Retractor	SL/Standard Length		EL/Extended Length	
	A	B	A	B
PNPTR, Packing Gland, Male NPT	40.5 (1029)	21.5 (546)	52.5 (1334)	33.5 (851)
P150R, Packing Gland, 150 lb Flange	40.5 (1029)	21.1 (536)	52.5 (1334)	33.5 (851)
P300R, Packing Gland, 300 lb Flange	40.5 (1029)	21.1 (536)	52.5 (1334)	33.1 (841)
P600R, Packing Gland, 600 lb Flange	40.5 (1029)	21.1 (536)	52.5 (1334)	33.1 (841)

Approximate Weight, lb (kg)

	SL	EL
PNPT	25 (11.5)	32 (14.5)
P150	30 (13.7)	37 (16.7)
P300	34 (15.5)	41 (18.5)
P600	35 (16.0)	42 (19.0)

Add 11 lb (5 kg) for remote electronics

PanaFlow MV82 Ordering Information

Parent Number Code

MV82 Insertion Multivariable Mass
Vortex Flowmeter

Feature 1: Multivariable Options

- V** Volumetric flowmeter for liquid, gas and steam
- VT** Velocity and temperature sensors
- VTP** Velocity, temperature and pressure sensors
- VT-EM** Energy output options
- VTP-EM** Energy options with pressure sensor

Feature 2: Probe Length

- SL** Standard length
- CL** Compact length
- EL** Extended length

Feature 3: Electronics Enclosure

- R (25)** Remote electronics Type 4X, 25 ft (8 m) cable
- R (50)** Remote electronics Type 4X, 50 ft (8 m) cable

Feature 4: Display Options

- DD** Digital Display and Programming Buttons
- ND** No Display

Feature 5: Input Power

- DC2** 12 to 36 VDC required on 2-wire (loop powered) meters with 1AHL only
- DC4** 12 to 36 VDC standard volumetric meter on 4-wire
- AC** 100-240 VAC, 50/60 Hz

Feature 6: Output Signal

- 1AHL** Loop powered option—one analog output (4-20 mA), one pulse, HART communication protocol - Must use DC2 input power
- 1AH** One analog output (4-20 mA), one alarm, one pulse, HART communication protocol
- 1AM** One analog output (4-20 mA), one alarm, one pulse, HART communication protocol
- 3AH** Three analog outputs (4-20 mA), three alarms, one pulse, HART, (VT, VTP only)
- 3AM** Three analog outputs (4-20 mA), three alarms, one pulse, MODBUS, (VT, VTP only)

Feature 7: Process Temperature Options

- ST** Standard process temperature -40° to 500°F (-40° to 260°C)
- HT** High process temperature 750°F (400°C)

Feature 8: Pressure Options

- P0** No pressure sensor
- P1** Maximum 30 psia (2 barg), Proof 60 psia (4 barg)
- P2** Maximum 100 psia (7 barg), Proof 200 psia (14 barg)
- P3** Maximum 300 psia (20 barg), Proof 600 psia (41 barg)
- P4** Maximum 500 psia (34 barg), Proof 1000 psia (64 barg)
- P5** Maximum 1500 psia (100 barg), Proof 2500 psia (175 barg)

Feature 9: Process Connections

- | | |
|---|---|
| CNPT Compression, 2 inch NPT | P40 Packing Gland, DN50 PN40 Flange |
| C150 Compression, 2 inch 150# Flange | P600 Packing Gland, 2 inch 600# Flange, Retractor |
| C16 Compression, DN50 PN16 Flange | |
| C300 Compression, 2 inch 300# Flange | P64 Packing Gland, DN50 PN64 Flange |
| C40 Compression, DN50 PN40 Flange | PNPTR Packing Gland, 2 inch NPT, Retractor |
| C600 Compression, 2 inch 600# Flange | P150R Packing Gland, 2 inch 150# Flange, Retractor |
| C64 Compression, 2 inch 600# Flange | P16R Packing Gland, DN50 PN16 Flange, Retractor |
| PNPT Packing Gland, 2 inch NPT | P300R Packing Gland, 2 inch 300# Flange, Retractor |
| P150 Packing Gland, 2 inch 150# Flange | P40R Packing Gland, 2 inch 300# Flange, Retractor |
| P16 Packing Gland, DN50 PN16 Flange | P600R Packing Gland, 2 inch 600# Flange, Retractor |
| P300 Packing Gland, 2 inch 300# Flange | P64R Packing Gland, DN50 PN64 Flange, Retractor |

MV82 - [] - [] - [] - [] - [] - [] - [] - [] - []



©2007 GE. All rights reserved.
920-405B

All specifications are subject to change for product improvement without notice. GE® is a registered trademark of General Electric Co. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with GE.